arXiv:1304.7420v1 [physics.acc-ph] 28 Apr 2013

Compensating the Electron Beam Energy Spread by the Natural Transverse Gradient of Laser Undulator in All-Optical X-ray Sources

Tong Zhang,[1] Chao Feng,[1] Haixiao Deng,[1, *] Dong Wang,[1] Zhimin Dai,[1] and Zhentang Zhao[1]
[1] *Shanghai Institute of Applied Physics, Chinese Academy of Sciences, Shanghai 201800, China*

(Dated: April 30, 2013)

All-optical schemes provide a potential to dramatically cut off the size and cost of x-ray light sources to the university-laboratory scale, with the combination of the laser-plasma accelerator and the laser undulator. However, the large longitudinal energy spread of the electron beam from laser-plasma accelerator may hinder the way to high brightness of these all-optical light sources. In this letter, the beam energy spread effect is proposed to be significantly compensated by the natural transverse gradient of a laser undulator when properly dispersing the electron beam transversely. Theoretical analysis and numerical simulations on conventional laser-Compton scattering sources and high-gain all-optical x-ray free-electron lasers with the electron beams from laser-plasma accelerators are presented.

PACS numbers: 41.60.Cr, 13.60.Fz, 07.85.Fv
Keywords: all-optical, x-ray source, TGLU, Compton scattering, FEL

X-ray continuously revolutionizes the understanding of the matters, and creates new sciences and technologies, which has been proven by 20 Nobel Prizes awarded for x-ray related works. Therefore, synchrotron radiation light sources and free-electron lasers (FELs) based on particle accelerators are being developed worldwide to satisfy the dramatically growing demands in the material and biological sciences [1]. More recently, the successful operation of the first FEL facilities in the XUV and hard x-ray regime announced the birth of the coherent x-ray science era [2–5]. However, considering the size and cost of these large-scale facilities, scientists begin to envision compact x-ray light sources [6–13] which may be popularized and afforded by the university-scale laboratories.

The marriage between the advanced laser technique and accelerators has contributed significantly to the miniaturization of the x-ray sources. On one hand, the developing of optical undulator shortens the period length to micrometer level [14, 15], and thus reduces the electron beam energy required by the x-ray light sources from several GeV to tens of MeV, e.g. the well-known laser-Compton scattering light sources [6, 11, 16–19]. On the other hand, the laser-plasma accelerators (LPAs) have made a great breakthrough in generating electron beam with peak current above 10 kA, low emittance less than 0.1 μm and beam energy of 1 GeV [20–25]. Taking the great advantages of the laser undulator and the LPA, novel table-top all-optical Compton gamma-ray source has been experimentally demonstrated [18]. And more recently, high-gain all-optical x-ray FELs are being under consideration [8, 9, 26, 27].

Currently, the electron beam from LPA usually has large energy spread with percent level, which may be the bottleneck for achieving high brightness in the x-ray light source applications. Thus, various great efforts have being made to reduce the energy spread in the LPA community [28, 29]. Meanwhile, in the light source community, the concept of transverse gradient undulator (TGU) proposed in FEL oscillator [30] has been recently suggested to overcome the electron beam energy spread in the high-gain FELs driven by LPAs and ultimate storage rings [31, 32]. In this Letter, we explore a novel concept for compensating the beam energy spread effect in the all-optical x-ray sources by using the nonlinear Gaussian distribution of laser, i.e., the controllable natural transverse gradient of the laser undulator (TGLU). Theoretical analysis and three-dimensional simulations indicate that the radiation pulses from TGLU boosted x-ray sources present orders of magnitude brightness enhancement when compared with normal all-optical sources driven by the LPA beams with large energy spread, due to its improvement in the power gain, the spatial and temporal patterns.

In order to generate table-top x-ray sources, all-optical scheme consists of the LPA electron beam and the laser undulator has been proposed. The principle of the laser undulator is more generally known as laser-Compton scattering, where the electrons with relativistic energy γ_0 scatter the laser photons with wavelength λ_l to a shorter wavelength λ_s at the expense of the electrons kinetic energy [33]. The interaction between the electron and the laser undulator can be described by the undulator resonant relation from the conventional theory of undulator radiation, i.e.,

$$\lambda_s = \frac{\lambda_u}{2\gamma_0^2}\left(1 + \frac{K_0^2}{2}\right) \tag{1}$$

The equivalent period length of the laser undulator λ_u is determined by the scattering angle ϕ of the electron beam and the laser by $\lambda_u = \lambda_l/(1 - \cos\phi)$, the dimensionless undulator parameter K could be written as $K = \frac{eE\lambda_u}{2\pi mc^2}$, where e, E, m and c is the elementary charge, the amplitude of laser field, the rest electron mass and the speed of light in vacuum. It is expected that



FIG. 1: (color online) *Left*: The electric field of laser undulator and the incident electron beam in the transverse plane, where $x^*o^*y^*$ and xoy is the coordinates of the laser undulator and the electron beam, respectively, σ_r is rms transverse radius of the laser undulator, x_0 is the centroid displacement between the electron beam and the laser undulator, '+/−' sign indicates that the electron beam is located at the right or left side of the origin o^*, the longitudinal coordinates z^* and z are perpendicular to the transverse plane. *Right*: the dimensionless strength parameter of the laser undulator with transverse nonlinear Gaussian gradient, and the (x, γ) phase-space of the electron beam with/without transverse dispersion.

K could reach $1-2$ with the stat-of-the-art laser technique [27, 34], and still be moving forward.

To clearly illustrate the transverse gradient of a laser undulator, we start from the case where the electron beam interacts with a counter-propagating laser undulator, i.e., $\phi = \pi$. The transverse field of the laser undulator can be seen in Figure 1., into which the electron beam is guided with a transverse displacement of x_0, thus in the electron beam frame, the undulator parameter felt by the electron at the position of x could be written as

$$K(x) = K_0 e^{-\frac{(x+x_0)^2 - x_0^2}{2\sigma_r^2}} \tag{2}$$

where $K_0 = K_m e^{-\frac{x_0^2}{2\sigma_r^2}}$ is the undulator parameter at the center of electron beam. Then the gradient of the laser undulator can be observed from the derivative of Eq. (2), reads,

$$\frac{\Delta K}{K} = -\frac{x_0}{\sigma_r^2}\Delta x \tag{3}$$

Thus, the equivalent transverse gradient of laser undulator could be written as $\alpha = -\frac{x_0}{\sigma_r^2}$, which can be controlled obviously by adjusting the laser beam size and the injection position of the electron beam. Under such circumstance, if the electron beam with large energy spread was properly dispersed by $x = \eta\Delta\gamma/\gamma$ in the transverse plane, with η the dispersion strength, the longitudinal spread effects of the electron beam could be converted to the transverse plane and could be potentially compensated.



FIG. 2: (color online) Calculated spectra of laser-Compton scattering with different strengths of transverse disperse. The energy of the cold beam is 45 MeV with energy spread of 1%, and the beam size of laser undulator is $\sigma_r = 100\,\mu$m, displacement between the laser and electron is $x_0 = -100\,\mu$m.

The essence of the TGLU on suppressing the beam energy spread effects can be learnt from the laser-Compton scattering process. Here we consider a $10\,\mu$m wavelength laser with $100\,\mu$m radius and 3.3 ps flat-top distribution in longitudinal, i.e., a laser undulator with period number $N_u = 100$, and a cold electron beam with energy of 45 MeV and energy spread of 1%, then an effective undulator strength $K_0 = 2.3$ results in radiation of 1 keV photon energy. According to the theory of undulator radiation, the bandwidth of 1 keV photon will be 1% for a fully cold electron beam, which however will be significantly broadened by a large beam energy spread. If the electron beam with a dispersion η was injected at $x_0 = -100\,\mu$m, the radiation spectrum on the beam axis can be calculated from the sum of the spontaneous emission spectrum of individual electrons. Figure 2. shows the radiation spectra with different dispersions to the electron beam, it is found that the radiation bandwidth is approximately 6 times improved with $\eta = 140\,\mu$m, when compared with the case of $\eta = 0\,\mu$m, which already achieves the theoretical limit of the undulator radiation.

It is universally known that the small-signal gain of a FEL is proportional to the derivative of the undulator spontaneous emission spectra, greatly depends on the beam energy detuning, i.e., $\Delta\gamma/\gamma_0$ [35]. In order to maximize the small-signal gain, in principle, $\Delta\gamma/\gamma_0$ should be kept as a constant with different x value. Then theoretically one can derive the optimal relationship between the TGLU and the dispersion as follows,

$$-\frac{x_0}{\sigma_r^2} = \frac{2+K_0^2}{\eta K_0^2} \tag{4}$$

In the cases of Figure 2., the gradient of the laser undulator is $10^5\,\mathrm{m}^{-1}$ and the Eq. (4) predicts the optimal dispersion of $140\,\mu$m, which is pretty consistent with the simulated results. Moreover, the spectra also demonstrate a maximum small-signal gain for the case of $140\,\mu$m dispersion.

Recently, it is reported that the powerful x-ray from high-gain Compton-scattering could be realizable by significantly extending the interaction length of the electron beam and the laser undulator, but a rather small beam energy spread of 5×10^{-5} was critically required [27]. Here we demonstrate the advantages of TGLU in the application of high-gain all-optical x-ray FELs, where the collision angle is $\phi=\pi/2$, then accordingly the transverse laser shape should be subtly manipulated to introduce the proper transverse gradient [27]. For the transversely dispersed electron beam in the laser undulator, taking the coupling reduction between the electron beam and the radiation into accounts, an effective FEL parameter can be defined as [31],

$$\rho_{\mathrm{T}} = \rho\left(1+\frac{\eta^2\sigma_\delta^2}{\sigma_x^2}\right)^{-\frac{1}{6}} \tag{5}$$

where σ_x is the electron beam radius, σ_δ is the fractional energy spread,ρ is the classical FEL parameter [36]. Assuming the average beta function of the LPA beam in laser undulator to be $\bar{\beta}=N_u\lambda_u/2$, then the FEL power gain length considering the transverse gradient of a laser undulator is:

$$L_g^{\mathrm{T}} \approx \frac{\lambda_u}{4\pi\sqrt{3}\rho_{\mathrm{T}}}\left(1+\left(\frac{K_0^2}{2+K_0^2}\right)^2\frac{x_0^2\epsilon_n N_u\lambda_u}{2\gamma\rho_{\mathrm{T}}^2\sigma_r^4}\right) \tag{6}$$

with N_u the total period number of laser undulator.

Eq. (6) gives the clue about the gain length shortening for relative large beam energy spread, which means the energy spread reduction could be compensated by TGLU. For instance, the LPA beam with energy spread of 1% and other parameters shown in Table I, the laser undulator with $x_0=\sigma_r=100\,\mu$m, dispersion $\eta=-140\,\mu$m will contribute 54% shortening to the FEL gain length.

Because of the continuous progress in the LPA community, we are optimistic about achieving the beam parameters shown in Table I. In order to illustrate the great potential of TGLU in the all-optical x-ray FELs, we present a detailed three-dimensional numerical simulation case here. The source code of GENESIS 1.3 [37] is modified to adapt the TGLU configuration. After the two-dimensional scan of the transverse dispersion η and the gradient α of the laser undulator, the optimal working condition $\eta=200\,\mu$m and $\alpha_{\mathrm{opt}}=8600\,\mathrm{m}^{-1}$ is found.

TABLE I: Parameters of high-gain Compton scattering all-optical x-ray source

Parameter	Symbol	Value	Unit
Beam Energy	E_b	60	MeV
Relative Energy Spread	σ_δ	0.5%	
Norm. Emittance	ϵ_n	0.02	μm
Beam size (rms)	σ_x	1.0	μm
Peak Current	I_p	3	kA
Laser wavelength	λ	10	μm
FEL photon energy	E_{ph}	1.0	keV



FIG. 3: (color online) Two dimensional optimization of the transverse position x_0 of the incident electron beam and the transverse radius σ_r of the laser undulator, the white dashed line indicated the optimal relationship between x_0 and σ_r with $x_0=-\alpha_{\mathrm{opt}}\sigma_r^2$, where α_{opt} is optimal gradient with regard to the optimal dispersion of $\eta=200\,\mu$m.

Furthermore, according to the theory of TGLU, with the optimal dispersion of $200\,\mu$m, multiple combination of (σ_r, x_0) could be operational. The simulation results in Figure 3. show the working zone highlighted by the fitted curve $x_0=-\alpha_{\mathrm{opt}}\sigma_r^2$, e.g. $\alpha_{\mathrm{opt}}=8600\,\mathrm{m}^{-1}$ for $(\sigma_r, x_0)=(100\,\mu\mathrm{m}, -86\,\mu\mathrm{m})$. It is worth to stress that the optimal working zone becomes larger as the transverse radius of the laser undulator increases, which could be clearly seen from $|\Delta x_0| = 2\alpha_{\mathrm{opt}}\sigma_r\Delta\sigma_r$.

Figure 4. shows the simulated FEL power growth around 1 keV photon energy for the normal laser undulator case and the TGLU case. For a SASE FEL, the power improvement of the TGLU case is almost 2 orders of magnitude for a 5 mm long laser-beam interaction length even though it is still far away from the FEL saturation. Further studies indicate that, for the case of 1% beam energy spread, 1 order of magnitude improvement



FIG. 4: (color online) Power gain curve for the case of 0.5% energy spread, in which the TGLU boosted case (blue solid line) shows an additional gain of 100-fold over the normal case (red solid line).

of FEL power can be achieved.

The transverse mode pattern can be seen from Figure 5. The transverse coherence is very poor because of the large energy spread and relatively low gain with absence of TGLU. While good transverse coherence is established because the transverse gradient allows for a weakly dispersed beam ($\sim 1\,\mu$m horizontal beam size) with TGLU boosted.



(a) Normal (b) TGLU

FIG. 5: (color online) Normalized transverse field pattern from all-optical x-ray light source, *left*: normal operational mode, *right*: working with TGLU.

In conclusion, a novel operation mode of all-optical x-ray light source was proposed with the electron beam from the advanced laser-plasma accelerator and laser undulator. Using the natural transverse gradient of the laser undulator, the beam energy spread impact to the power gain of x-ray source could be effectively compensated. The theory and numerical simulation indicate that the optimal working condition could be found with different transverse radius of laser undulator and the electron beam incident position. The utilization of TGLU in the laser-Compton scattering shows the great advantage of almost orders brightness enhancement by narrowing the bandwidth. The high-gain all-optical x-ray FEL source example shows that with the laser beam size of hundreds μm, TGLU could increase the output power by about 2 orders of magnitude with much better transverse field pattern. It is convinced that the natural transverse gradient of the laser undulator holds great potential in developing table-top all-optical x-ray light sources, and it also can be extended to the applications in the radiofrequency and terahertz undulators.

The authors are grateful to Chao Chang, Lei Shen, Dazhang Huang, Bo Liu and Bocheng Jiang for helpful discussions. This work was partially supported by the Major State Basic Research Development Program of China (2011CB808300) and the National Natural Science Foundation of China (11175240 and 11205234).

---

* denghaixiao@sinap.ac.cn

[1] B. W. J. McNeil and N. R. Thompson, Nat. Photonics **4**, 814 (2010).
[2] W. Ackermann, G. Asova, V. Ayvazyan, *et al.*, Nat. Photonics **1**, 336 (2007).
[3] E. Allaria, R. Appio, L. Badano, *et al.*, Nat. Photonics **6**, 699 (2012).
[4] P. Emma, R. Akre, J. Arthur, *et al.*, Nat. Photonics **4**, 641 (2010).
[5] T. Ishikawa, H. Aoyagi, T. Asaka, *et al.*, Nat. Photonics **6**, 540 (2012).
[6] R. W. Schoenlein, W. P. Leemans, A. H. Chin, *et al.*, Science **274**, 236 (1996).
[7] H. P. Schlenvoigt, K. Haupt, A. Debus, *et al.*, Nat. Phys. **4**, 130 (2007).
[8] F. Grner, S. Becker, U. Schramm, *et al.*, Appl. Phys. B: Lasers Opt. **86**, 431 (2007).
[9] K. Nakajima, Nat. Phys. **4**, 92 (2008).
[10] M. Fuchs, R. Weingartner, A. Popp, *et al.*, Nat. Phys. **5**, 826 (2009).
[11] P. Sprangle, B. Hafizi, and J. Peano, Phys. Rev. Spec. Top.–Accel. Beams **12** (2009).
[12] S. Kneip, C. McGuffey, J. L. Martins, *et al.*, Nat. Phys. **6**, 980 (2010).
[13] J. Dai, H. Deng, and Z. Dai, Phys. Rev. Lett. **108**, 034802 (2012).
[14] J. Gea-Banacloche, G. Moore, R. Schlicher, *et al.*, IEEE J. Quantum Electron. **23**, 1558 (1987).
[15] A. Bacci, C. Maroli, V. Petrillo, *et al.*, Nucl. Instrum. Methods Phys. Res., Sect. A **587**, 388 (2008).
[16] S. Kashiwagi, R. Kato, G. Isoyama, *et al.*, Radiat. Phys. Chem. **78**, 1112 (2009).
[17] G. A. Krafft and G. Priebe, Rev. Accel Sci. Technol. **03**, 147 (2010).
[18] K. T. Phuoc, CordeS, ThauryC, *et al.*, Nat Photon **6**, 308 (2012).
[19] S. Chen, N. D. Powers, I. Ghebregziabher, *et al.*, Phys. Rev. Lett. **110**, 155003 (2013).
[20] W. P. Leemans, B. Nagler, A. J. Gonsalves, *et al.*, Nat. Phys. **2**, 696 (2006).
[21] O. Lundh, J. Lim, C. Rechatin, *et al.*, Nat. Phys. **7**, 219

(2011).
[22] S. Fritzler, E. Lefebvre, V. Malka, *et al.*, Phys. Rev. Lett. **92**, 165006 (2004).
[23] E. Brunetti, R. P. Shanks, G. G. Manahan, *et al.*, Phys. Rev. Lett. **105**, 215007 (2010).
[24] J. S. Liu, C. Q. Xia, W. T. Wang, *et al.*, Phys. Rev. Lett. **107**, 035001 (2011).
[25] G. R. Plateau, C. G. R. Geddes, D. B. Thorn, *et al.*, Phys. Rev. Lett. **109**, 064802 (2012).
[26] V. Petrillo, L. Serafini, and P. Tomassini, Phys. Rev. Spec. Top.–Accel. Beams **11**, 070703 (2008).
[27] C. Chang, C. Tang, and J. Wu, Phys. Rev. Lett. **110**, 064802 (2013).
[28] C. G. R. Geddes, C. Toth, J. van Tilborg, *et al.*, Nature **431**, 538 (2004).
[29] J. Faure, Y. Glinec, A. Pukhov, *et al.*, Nature **431**, 541 (2004).
[30] T. I. Smith, J. M. J. Madey, L. R. Elias, *et al.*, J. Appl. Phys. **50**, 4580 (1979).
[31] Z. Huang, Y. Ding, and C. B. Schroeder, Phys. Rev. Lett. **109**, 204801 (2012).
[32] Y. Cai, Y. Ding, R. Hettel, *et al.*, SLAC-PUB-15380 (2013).
[33] A. H. Compton, Phys. Rev. **21**, 483 (1923).
[34] D. Du, X. Liu, G. Korn, *et al.*, Appl. Phys. Lett. **64**, 3071 (1994).
[35] J. M. J. Madey, J. Appl. Phys. **42**, 1906 (1971).
[36] R. Bonifacio, C. Pellegrini, and L. M. Narducci, Opt. Commun. **50**, 373 (1984).
[37] S. Reiche, Nucl. Instrum. Methods Phys. Res., Sect. A **429**, 243 (1999).